

GRAFPROTECT

Protection of porous materials against graffiti and paint stains in general.



TECNADIS
PRS PERFORMANCE



TECNADIS
GRAFPROTECT



ANTIGRAFFITI
PERMANENT



TECNADIS GRAFPROTECT

FEATURES

ANTIGRAFFITI SOLUTION BASED ON NANOTECHNOLOGY, protects the surfaces against paints, markers, graffiti, etc., making it easy the cleaning and removal by common and low-cost processes.

With **WATER AND OIL REPELLENT effect**, It protects against wáter, oil and stains in general.

It forms a **RESISTANT FILM**, preventing the paint from penetrating the surface.

IT RESISTS MORE THAN 10 CLEANING CYCLES

TOTALLY REAPPLICABLE, it is not necessary to remove previous treatments.

The active compounds do **not react with the treated surface**, maintaining the substrate unaltered.



TECNADIS GRAFPROTECT

Suitable for the surface treatment of terrazzo, marble, granite, concrete, ceramic (brick, tiles), sandstone, and in general any constructive substrate, both in exterior and interior applications.

APPROXIMATED YIELD (*):

MATERIAL	TOTAL (ml/m ²)	TOTAL* (m ² /l)
Marble and low porous limestone, terrazzo, polished concrete.	60-75	15-17
Granite, facing brick, non-polished concrete, tiles.	70-80	12,5-15
Sandstone, coarse concrete, high porous limestone.	80-100	10-12,5

* Depending on the material porosity

TECHNICAL DATA

- **Drying to touch times:** 30 - 60 min
- **Complete drying time:** 48 hours
- **Pot-life:** the mixture remains active for up to 48 hours after mixing, in a closed container

APPLICATION: 4 steps

STEP 1: Cleaning and preparation of the substrate.

The Surface must be completely clean and dry before application.

STEP 2: PRIMER application.

Apply by spraying (example: AIRLESS). Apply only a light coat (not saturation). Let dry between 30 min and 60 min. before step 4.

STEP 3: GRAFPROTECT preparation.

It is supplied in a 1:4 ratio so that the content of the container labelled ACTIVATOR is poured into the container labelled PROTECTOR. Mix and shake.



STEP 4: GRAFPROTECT application.

Apply with brush, roller or spraying equipment. The entire surface must be covered by uniform saturation of the surface. The optimal effect is achieved after 48 hours from application.

TECNADIS GRAFPROTECT

FORMATS

TECNADIS GRAFPROTECT 1:4



1 LITRE

5 LITRES

25 LITRES

OTHER «TECNADIS» RANGE PRODUCTS for Construction, Rehabilitation and Maintenance.

TECNADIS PRS PERFORMANCE

Water and oil repellent for floors or pavements.
Abrasion resistant.



Formats: 1L, 5L, 25L

AQUASHIELD ULTIMATE

Hydrophobic product of high performance for
vertical and tilted surfaces.



Formats: 1L, 5L, 25L

TECNADIS SELF CLEAN-ULTRA

Solution for static glass that
generates self-cleaning
surfaces



TECNOLOGÍA NAVARRA DE NANOPRODUCTOS S.L.

Área Industrial Perguita, Calle A Nº1
31210 Los Arcos (Navarra) - Spain

Tel.: +34 948 640 318 - Fax: +34 948 640 319

www.tecnan-nanomat.es
tecnan@tecnan-nanomat.es