

TECNAN – DECOMPOSED RATES 2024 (Prices for Spain)

CODE	UNIT	SUMMARY	QUANTITY	PRICE	SUBTOTAL	SUM
R07J020	m2	WATER REPELLENT FOR VERTICAL ELEMENTS HIGH POROSITY NANOPARTICLES <u>AQUASHIELD ULTIMATE</u> On-site application of hydrophobic coating for facades and other vertical or tilted surfaces of high porosity, based on oxide nanoparticles, non-filmogenic, totally permeable, unalterable to UV radiation, transparent and re-applicable AQUASHIELD ULTIMATE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with medium-high porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; etc.). Approximate yield of 5m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G150	l	Water repellent with nanoparticles Aquashield Ultimate	0,200	15,27	3,05	
%PM0150	%	Small Material	0,073	1,50	0,11	
TOTAL						7,41
R07J030	m2	WATER REPELLENT FOR VERTICAL ELEMENTS LOW POROSITY NANOPARTICLES <u>AQUASHIELD ULTIMATE</u> On-site application of hydrophobic coating for facades and other vertical or tilted surfaces of low porosity, based on oxide nanoparticles, non-filmogenic, totally permeable, unalterable to UV radiation, transparent and re-applicable AQUASHIELD ULTIMATE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with low porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; etc.). Approximate yield of 7m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G150	l	Water repellent with nanoparticles Aquashield Ultimate	0,140	15,27	2,14	
%PM0160	%	Small Material	0,064	1,60	0,10	
TOTAL						6,49
R07J080	m2	WATER REPELLENT FOR VERTICAL ELEMENTS HIGH POROSITY NANOPARTICLES <u>AQUASHIELD FORTE</u> On-site application of hydrophobic coating for facades and other vertical or tilted surfaces of high porosity, based on oxide nanoparticles, non-filmogenic, totally permeable, unalterable to UV radiation, transparent and re-applicable AQUASHIELD FORTE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with medium-high porosity (facing brick; single-layer mortar, concrete, prefabricated, natural stones and mixed surfaces in which different materials and porosities are mixed). Approximate yield of 5m2/l, substrate preparation is not included. Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G152	l	Water repellent with nanoparticles Aquashield Forte	0,200	17,28	3,46	
%PM0140	%	Small Material	0,077	1,40	0,11	
TOTAL						7,82
R07J090	m2	WATER REPELLENT FOR VERTICAL ELEMENTS LOW POROSITY NANOPARTICLES <u>AQUASHIELD FORTE</u> On-site application of hydrophobic coating for facades and other vertical or tilted surfaces of low porosity, based on oxide nanoparticles, non-filmogenic, totally permeable, unalterable to UV radiation, transparent and re-applicable AQUASHIELD FORTE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with low porosity (facing brick; single-layer mortar, concrete, prefabricated, natural stones and mixed surfaces in which different materials and porosities are mixed). Approximate yield of 7 m2/l, substrate preparation is not included. Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G152	l	Water repellent with nanoparticles Aquashield Forte	0,140	17,28	2,42	
%PM0150	%	Small Material	0,067	1,50	0,10	
TOTAL						6,77

TECNAN – DECOMPOSED RATES 2024 (Prices for Spain)

CODE	UNIT	SUMMARY	QUANTITY	PRICE	SUBTOTAL	SUM
R08H120	m2	ANTIBACTERIAL WATER REPELLENT FOR VERTICAL ELEMENTS <u>HIGH POROSITY NANOPARTICLES</u> AQUASHIELD ACTIVE On-site application of hydrophobic coating with antibacterial effect for facades and other vertical or tilted surfaces of high porosity, based on oxide nanoparticles, non-filmogenic, totally permeable, unalterable to UV radiation, transparent and re-applicable AQUASHIELD ACTIVE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with medium-high porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; etc.). Approximate yield of 5m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G161	l	Antibacterial water repellent with nanoparticles Aquashield Active	0,200	17,93	3,59	
%PM0150	%	Small Material	0,078	1,50	0,12	
TOTAL						7,96

R08H130	m2	ANTIBACTERIAL WATER REPELLENT FOR VERTICAL ELEMENTS <u>LOW POROSITY NANOPARTICLES</u> AQUASHIELD ACTIVE On-site application of hydrophobic coating with antibacterial effect for facades and other vertical or tilted surfaces of low porosity, based on oxide nanoparticles, non-filmogenic, totally permeable, unalterable to UV radiation, transparent and re-applicable AQUASHIELD ACTIVE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with low porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; etc.). Approximate yield of 7m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G161	l	Antibacterial water repellent with nanoparticles Aquashield Active	0,140	17,93	2,51	
%PM0160	%	Small Material	0,068	1,60	0,11	
TOTAL						6,87

R07J060	m2	WATER-BASED WATER REPELLENT FOR VERTICAL ELEMENTS <u>HIGH POROSITY NANOPARTICLES</u> AQUAPORE FORTE On-site application of water-based hydrophobic coating for facades and other vertical or tilted surfaces of high porosity, based on oxide nanoparticles, non-filmogenic, totally permeable, unalterable to UV radiation, transparent and re-applicable AQUAPORE FORTE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with medium-high porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; etc.). Approximate yield of 5m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G160	l	Water-based water repellent with nanoparticles Aquapore Forte	0,200	17,28	3,46	
%PM0130	%	Small Material	0,077	1,30	0,10	
TOTAL						7,81

R07J070	m2	WATER-BASED WATER REPELLENT FOR VERTICAL ELEMENTS <u>LOW POROSITY NANOPARTICLES</u> AQUAPORE FORTE On-site application of water-based hydrophobic coating for facades and other vertical or tilted surfaces of low porosity, based on oxide nanoparticles, non-filmogenic, totally permeable, unalterable to UV radiation, transparent and re-applicable AQUAPORE FORTE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with low porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; etc.). Approximate yield of 7m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G160	l	Water-based water repellent with nanoparticles Aquapore Forte	0,140	17,28	2,42	
%PM0150	%	Small Material	0,067	1,50	0,10	
TOTAL						6,77

TECNAN – DECOMPOSED RATES 2024 (Prices for Spain)

CODE	UNIT	SUMMARY	QUANTITY	PRICE	SUBTOTAL	SUM
R07J040	m2	WATER AND OIL REPELLENT <u>HIGH POROSITY NANOPARTICLES PRS PERFORMANCE</u> On-site application of hydrophobic and oleophobic (anti-stain) coating for any type of horizontal surfaces such as floors, pavements (also applicable to facades) with high porosity, based on oxide nanoparticles, non-filmogenic, high permeability, unalterable to UV radiation, highly resistant to abrasion and re-applicable TECNADIS PRS PERFORMANCE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with medium-high porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; alabaster; plaster; terrazzo; etc.). Approximate yield of 6m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G155	l	Water and oil repellent with nanoparticles Tecnadis PRS Performance	0,170	22,99	3,91	
%PM0130	%	Small Material	0,082	1,30	0,11	
TOTAL						8,27
R07J050	m2	WATER AND OIL REPELLENT <u>LOW POROSITY NANOPARTICLES PRS PERFORMANCE</u> On-site application of hydrophobic and oleophobic (anti-stain) coating or any type of horizontal surfaces such as floors, pavements (also applicable to facades) with low porosity, based on oxide nanoparticles, non-filmogenic, high permeability, unalterable to UV radiation, highly resistant to abrasion and re-applicable TECNADIS PRS PERFORMANCE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with low porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; alabaster; plaster; terrazzo; etc.). Approximate yield of 9m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G155	l	Water and oil repellent with nanoparticles Tecnadis PRS Performance	0,110	22,99	2,53	
%PM0150	%	Small Material	0,068	1,50	0,10	
TOTAL						6,88
R08H140	m2	WATER AND OIL REPELLENT <u>HIGH POROSITY NANOPARTICLES PRS PERFORMANCE EC (Special Colour)</u> On-site application of hydrophobic and oleophobic (anti-stain) coating with colour enhancing, for any type of horizontal surfaces such as floors, pavements (also applicable to facades) with high porosity, based on oxide nanoparticles, non-filmogenic, high permeability, unalterable to UV radiation, highly resistant to abrasion and re-applicable TECNADIS PRS PERFORMANCE EC (Special Colour) by TECNAN; consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with medium-high porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; alabaster; plaster; terrazzo; etc.). Approximate yield of 6m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G162	l	Water and oil repellent with colour enhancing Tecnadis PRS Performance EC (Special Colour)	0,170	27,21	4,63	
%PM0130	%	Small Material	0,089	1,30	0,12	
TOTAL						9,00
R08H150	m2	WATER AND OIL REPELLENT <u>LOW POROSITY NANOPARTICLES PRS PERFORMANCE EC (Special Colour)</u> On-site application of hydrophobic and oleophobic (anti-stain) coating with colour enhancing, for any type of horizontal surfaces such as floors, pavements (also applicable to facades) with low porosity, based on oxide nanoparticles, non-filmogenic, high permeability, unalterable to UV radiation, highly resistant to abrasion and re-applicable TECNADIS PRS PERFORMANCE EC (Special Colour) by TECNAN; consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with low porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; alabaster; plaster; terrazzo; etc.). Approximate yield of 9m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G162	l	Water and oil repellent with colour enhancing Tecnadis PRS Performance EC (Special Colour)	0,110	27,21	2,99	
%PM0150	%	Small Material	0,072	1,50	0,11	
TOTAL						7,35

TECNAN – DECOMPOSED RATES 2024 (Prices for Spain)

CODE	UNIT	SUMMARY	QUANTITY	PRICE	SUBTOTAL	SUM
R08H160	m2	WATER-BASED WATER AND OIL REPELLENT HIGH POROSITY NANOPARTICLES PRS PERFOPORE On-site application of water-based hydrophobic and oleophobic (anti-stain) coating for any type of horizontal surfaces such as floors, pavements (also applicable to facades) with high porosity, based on oxide nanoparticles, non-filmogenic, high permeability, unalterable to UV radiation, highly resistant to abrasion and re-applicable TECNADIS PRS PERFOPORE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with medium-high porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; alabaster; plaster; terrazzo; etc.). Approximate yield of 6m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G163	l	Water-based water and oil repellent with nanoparticles Tecnadis PRS Perfopore	0,170	28,93	4,92	
%PM0130	%	Small Material	0,092	1,30	0,12	
TOTAL						9,29
R08H170	m2	WATER-BASED WATER AND OIL REPELLENT LOW POROSITY NANOPARTICLES PRS PERFOPORE On-site application of water-based hydrophobic and oleophobic (anti-stain) coating for any type of horizontal surfaces such as floors, pavements (also applicable to facades) with low porosity, based on oxide nanoparticles, non-filmogenic, high permeability, unalterable to UV radiation, highly resistant to abrasion and re-applicable TECNADIS PRS PERFOPORE by TECNAN, consisting in applying 2 coats of product by spraying (preferably), brush or roller, on exterior or interior surfaces of materials with low porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; alabaster; plaster; terrazzo; etc.). Approximate yield of 9 m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33G163	l	Water-based water and oil repellent with nanoparticles Tecnadis PRS Perfopore	0,110	28,93	3,18	
%PM0150	%	Small Material	0,074	1,50	0,11	
TOTAL						7,54
R08F070	m2	NATURAL STONE CONSOLIDANT BASED ON ETHYL SILICATE TECNADIS SOLIDUS Natural stone consolidation treatment, of general application with special emphasis on degraded areas, including: application of consolidant solution based on silicic ester (ethyl silicate), TECNADIS SOLIDUS by TECNAN, applied by spraying, brush, injection or immersion, making it penetrate into interstices and joints, which increases the hardness of the stone allowing the transpiration of water vapour. In accordance with technical report, specifications, manufacturer's recommendations, plans and project specifications. Average yield of 4m2/l. Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33DF180	l	Consolidant based on ethyl silicate Tecnadis Solidus	0,250	19,55	4,89	
%PM0130	%	Small Material	0,091	1,30	0,12	
TOTAL						9,26
R07LF020	m2	PERMANENT ANTI-GRAFFITI HIGH POROSITY SURFACES NANOPARTICLES GRAFPROTECT Bi-component, nanotechnology-based permanent anti-graffiti protective treatment for facades and other vertical or tilted surfaces with high porosity, with total resistance to UV radiation, breathable, highly resistant to abrasion and re-applicable TECNADIS GRAFPROTECT by TECNAN. Suitable for both exterior and interior surfaces of materials with medium-high porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; alabaster; plaster; etc.). Approximate yield of 14 m2/l. Apply according to the manufacturer's specific instructions including primer and GRAFPROTECT treatment by sprayer or air spray gun (recommended standard low-pressure airless), brush or roller. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33J300	l	Anti-graffiti with nanoparticles Tecnadis Grafprotect	0,070	85,49	5,98	
%PM0070	%	Small Material	0,102	0,70	0,07	
TOTAL						10,30

TECNAN – DECOMPOSED RATES 2024 (Prices for Spain)

CODE	UNIT	SUMMARY	QUANTITY	PRICE	SUBTOTAL	SUM
R07LF030	m2	PERMANENT ANTI-GRAFFITI LOW POROSITY SURFACES NANOPARTICLES GRAFPROTECT Bi-component, nanotechnology-based permanent anti-graffiti protective treatment for facades and other vertical or tilted surfaces with low porosity, with total resistance to UV radiation, breathable, highly resistant to abrasion and re-applicable TECNADIS GRAFPROTECT by TECNAN. Suitable for both exterior and interior surfaces of materials with low porosity (natural stone: marble, limestone, granite, sandstone; brick; mortar; concrete; alabaster; plaster; etc.). Approximate yield of 17 m2/l. Apply according to manufacturer's specific instructions including primer and GRAFPROTECT treatment by sprayer or air spray gun (recommended standard low-pressure airless), brush or roller. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,100	22,22	2,22	
O01OA060	h	Labourer	0,100	20,27	2,03	
P33J300	l	Anti-graffiti with nanoparticles Tecnadis Grafprotect	0,059	85,49	5,04	
%PM0080	%	Small Material	0,093	0,80	0,07	
TOTAL						9,36
R07LH010	m2	HYDROPHILIC TREATMENT ANTI-DUST NANOTECHNOLOGY-BASED CLEANING/MAINTENANCE EXTERNAL GLASS SELFCLEAN-ULTRA Self-cleaning hydrophilic protective treatment with anti-dust effect, nanotechnology-based, for any type of external glass structure (facades, curtain walls, windows, shop windows, etc.), transparent, easy-to-apply and ultra-fast drying, highly resistant to UV radiation and other atmospheric agents, re-applicable, TECNADIS SELFCLEAN-ULTRA by TECNAN; consisting in applying a single layer of product with spray gun (preferably) by suction or pressure, following manufacturer's instructions. Approximate yield of 25 m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,050	22,22	1,11	
O01OA060	h	Labourer	0,050	20,27	1,01	
P33I250	l	Hydrophilic treatment with nanoparticles external glass Selfclean-Ultra	0,040	53,15	2,13	
%PM0240	%	Small Material	0,043	2,40	0,10	
TOTAL						4,35
R07LH020	m2	HYDROPHOBIC TREATMENT NANOTECHNOLOGY-BASED CLEANING/MAINTENANCE EXTERNAL GLASS VETROSMART Hydrophobic protective treatment based on nanotechnology that repels liquids and other substances for any type of external glass structure (facades, curtain walls, windows, shop windows, etc.), transparent, easy-to-apply and ultra-fast drying, fully resistant to UV radiation and other atmospheric agents, re-applicable, VETROSMART by TECNAN; consisting in applying a single layer of product with spray gun (preferably) by suction or pressure, following manufacturer's instructions. Approximate yield of 60 m2/l. No preparation of the substrate is required except for a standard cleaning (not included). Measurement of executed surface.				
O01OA030	h	Skilled tradesperson	0,050	22,22	1,11	
O01OA060	h	Labourer	0,050	20,27	1,01	
P33I255	l	Hydrophobic treatment with nanoparticles external glass Vetrosmart	0,017	109,00	1,85	
%PM0260	%	Small Material	0,040	2,60	0,10	
TOTAL						4,07
E27HS101	m2	MULTISURFACE PROTECTIVE COATING TECNADIS MULTICOAT (CLASSIC AND ULTRAKER) Non-stick ceramic nano protector with easy-to-clean and high hardness properties for metal, porcelain, plastic or painted surfaces, TECNADIS MULTICOAT by TECNAN. Based on a dispersion of ceramic nanoparticles that creates a non-stick protective layer, transparent or coloured (black or forge grey). Prevents premature deterioration caused by exposure to the elements (water, ice, humidity, rust, saltpetre, corrosion, UV radiation, etc.) or by human action (oil, grease, graffiti, scratches, stickers, urine, etc.). To be applied as a protective surface layer on metal structures, doors, windows, gates, lampposts, railings, etc. The surface must be clean, degreased, oxidation-free and dry. Application with spray gun (preferably), brush or roller. Application and preparation of the substrate as specified in the product data sheet. Price for 1 litre container. Approximate yield 15 m2/l. Measurement of executed surface.				
O01OB230	h	Skilled painter	0,100	22,22	2,22	
O01OB240	h	Painter assistant	0,100	20,53	2,05	
P25RO301	l	Multisurface protective coating with nanoparticles Tecnadis Multicoat	0,066	66,39	4,38	
%PM0080	%	Small Material	0,087	0,80	0,07	
TOTAL						8,72

TECNAN – DECOMPOSED RATES 2024 (Prices for Spain)

CODE	UNIT	SUMMARY	QUANTITY	PRICE	SUBTOTAL	SUM
E27HA181	m2	PROTECTIVE COATING FOR METALS NANOPARTICLES TECNADIS MULTICOAT ANTICORROSION (PRIMER AND FINISH) Anti-corrosion ceramic nano protector, TECNADIS MULTICOAT ANTICORROSION by TECNAN, to be applied directly on metal, as an anti-corrosion primer that can be overcoated with other paint layers or as the only protective layer. Based on a dispersion of ceramic and metallic nanoparticles that provide advanced and long-lasting cathodic protection (Category C4) with a metallic grey finish, high hardness, high adhesion, with the option of including non-stick properties. Protects against corrosion, impact and scratching on all types of metal surfaces such as stainless steels, carbon/sanded steels, galvanised steel, iron, brass, aluminium, copper, bronze, etc. The surface must be clean and corrosion-free, although it can also be applied on lightly rusted metals. Application of 2 coats with spray gun (preferably), brush or roller. Application and preparation of the substrate as specified in the product data sheet. Price for 1 litre container. Approximate yield 10 m2/l. Measurement of executed surface.				
O01OB230	h	Skilled painter	0,100	22,22	2,22	
O01OB240	h	Painter assistant	0,100	20,53	2,05	
P25RI091	l	Protective coating for metals with nanoparticles Tecnadis Multicoat Anticorrosion	0,100	66,39	6,64	
%PM0080	%	Small Material	0,109	0,80	0,09	
TOTAL						11,00